




VMOTO

VS2

ELECTRIC VEHICLES


VMOTO
FLEET

**LIGHTWEIGHT, RELIABLE,
ECO-FRIENDLY**



Scan here
for more info

TECHNICAL INFORMATION

Homologation	L1e-B (comparable to 50cc)	Loading capacity	84 units
Engine	Vmoto	LxWxH	1940 mm*730 mm*1160 mm
Rated power	2.0 kW	Wheelbase	1327 mm
Max power	2.4 kW	Ground clearance	145 mm
Battery model	Polimer lithium battery	Seat height	780 mm
Battery capacity	60 V/45 Ah x 1 PC	Rims	Fr. 1.85-16 Rr. 2.5-14
Charging time	6 h (Normal charger) 3.5 h (Fast charger)	Tires	Fr. 90/80-16 Rr. 90/90-14
Charging power	1000 W (Fast charger) 600 W (Normal charger)	Suspension	Hydraulic damping system
Range*	80 Km*	Weight	83 kg (without battery)
Max speed	45 Km/h	Brakes	CBS
Climbing angle	14°	Colours	White (customizable)

WMTC Stage 3*





HAPPINESS IS A JOURNEY

VMOTO.COM

Vmoto Limited

Level 48, 152-158
St Georges Terrace,
Perth Western Australia 6000, Australia

Vmoto International

15, Zhongxing East Road
Lishui Economic Development Zone
Lishui District, Nanjing 211200
Jiangsu Province, China

Vmoto Europe

Boekweitstraat 95-97, 2153 GK
Nieuw Vennep, The Netherlands

Vmoto Italy Srl

Sesto S. Giovanni
(Milan)

Vmoto Germany

Ammerbuch (Stuttgart)

Vmoto UK

Guildford (London)

Vmoto France

Paris



Official
Electric Scooter
Supplier



OFFICIAL PARTNER



Attention: The photos and technical information contained in this catalog may refer to prototypes subject to changes during production and are for purely illustrative and reference purposes, therefore they are not binding for Vmoto International. Vmoto cannot be held responsible for any printing and/or translation errors. This catalog is transnational and therefore some products may not be available and/or their characteristics may vary according to local laws. Not all colors and versions are available in every country. Vmoto reserves the right to make changes and improvements to any product without prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the relevant user manuals. The products represented are not final versions and are therefore subject to significant changes at the discretion of Vmoto without notice. The photographs published in this catalog show only professional drivers in controlled road conditions. Do not try to imitate this driving behavior as it could be dangerous for you or other people on the road. This catalogue, including, but not limited to, trademarks, logos, texts, images, graphics and table of contents, constitutes the intellectual property of Vmoto, or in any case Vmoto has the right to reproduce it. Any total or partial reproduction, modification or other use of the catalog or its contents is prohibited, including publication on the internet without the prior written consent of Vmoto. Actual battery consumption may vary based on many factors, including, but not limited to, riding style, maintenance performed, weather conditions, surface characteristics, tire pressure, load, rider weight and the passenger, the accessories. Curb weights are considered with all operating fluids, standard equipment and battery. For more information visit www.vmotosoco.com.