





SOLIDITY, SAFETY AND STRENGTH.

Clean lines and an entirely new color range: CITI is bound to make its way in the B2C world. User friendly reverse function; double calipers extend brakes lifetime 3 times more; unbreakable foot-steps, protect the body parts.

L1e - L3e Max speed 80 km/h. Range L1e 80 Km*- L3e 70 km* Maximum Power 4.4 kW



Scan here for more info

TECHNICAL INFORMATION

THE FAST CITI

Homologation	L1e-B L3e-A1 (comparable to a 50cc, 125cc.)		
Engine	Vmoto	LxWxH	1940 mm*730 mm*1160 mm
Rated Power	2 kW (L1e-B) / 3.5 or 4.0 kW (L3e-A1)	Wheelbase	1327 mm
Maximum Power	2.4 kW (L1e-B) / 4.1 or 4.4 kW (L3e-A1)	Ground clearance	130 mm
Battery model	Polymer Lithium battery	Seat height	770 mm
Battery capacity	60 V/45 Ah or 74 V/28 Ah (optional 2 batteries)	Rims	Fr. 1.85-16 Rr. 2.5-14
Charging time	6 h for 2 batteries (3 h fast charge)	Tires	Fr. 90/80-16 Rr. 90/90-14
Charging power	60 V/45 Ah: 0.48 W - 0.9 W (fast charger) 74 V/28 Ah: 0.72 W - 1.4 KW (fast charger)	Suspension	Hydraulic damping system
Range*	L1e 80 Km* (100 Km* with 2 batteries) L3e 70 Km* (100 Km* with 2 batteries)	Weight	92 kg (without battery) 60 V/45 Ah: 18 Kg 74 V/28 Ah: 13 Kg/PCS
Max. Speed	L1e 45 km/h L3e 80 km/h	Brakes	CBS
Climbing angle	14°	Colours	Matte Black / Red / White / Matte Blue

*rider weight 75 kg with two batteries. WMTC Stage 3.



Happiness is a journey

VMOTO.COM

Vmoto Limited

Level 48, 152-158 St Georges Terrace, Perth Western Australia 6000, Australia

Vmoto International

15, Zhongxing East Road Lishui Economic Development Zone Lishui Discrict, Nanjing 21 1200 Jiangsu Province, China

Vmoto Europe

Boekweitstraat 95-97, 2153 GK Nieuw Vennep, The Netherlands

Vmoto Italy

Sesto S. Giovanni (Milan)

Vmoto Germany

Ammerbuch (Stuttgart)

Vmoto UK

Guildford (London)

Vmoto France

Paris







Attention: The photos and technical information contained in this catalog may refer to prototypes subject to changes during production and are for purely illustrative and reference purposes, therefore they are not binding for Vmoto International. Vmoto cannot be neit responsible for any printing and/or translation errors. This catalog is transnational and therefore some products any on the available and/or their characteristics may vary according to local laws. Not all colors and versions are available in every country. Vmoto reserves the night to make changes and improvements to any product without prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the relevant user manuals. The products represented are not final versions and are therefore subject to significant changes at the discretion of Vmoto without notice. By products applied in this catalog show only professional drivers in controlled road conditions. Do not try to imitate this driving behavior, in the catalog or the catalog or in any tasse Vmoto and a may be added the controlled or any tasse Vmoto and a may be added the controlled or any tasse Vmoto and the product of the catalog or its contents is prohibited, including publication on the internet without and present product or continued to including, but not intered to, including, but not intered to, including, but not intered to, including style, main-tenance performed, weather conditions, surface characteristics, the pressure, load, rider velocity and the passessor. Curb weights are considered with all operating fluids, standards equipment and stately represent the accessories. Curb weights are considered with all operating fluids, standards equipment and stately including, but not intered to, indired to, indirect to the controlled to the product of the controlled to the product of the controlled to the controlled to the controlled to the controlled to the cont