



● Blue

● Black

TECHNICAL INFORMATION

Homologation	L1e-B L3e-A1 (comparable to a 50cc, 125cc)	Climbing angle	18°
Engine	VMOTO	Weight	85 Kg (72 V/48 Ah battery) 80 Kg (72 V/32 Ah battery)
Rated power	4.0 kW	LxWxH	1970 mm*780 mm*1080 mm
Max power	8.0 kW	Wheelbase	1310 mm
Battery model	21700 cylindrical lithium battery	Ground clearance	270 mm
Battery capacity	72 V/48 Ah or 72 V/32 Ah	Seat height	840 mm
Charging time	2.5 h (72 V/32 Ah) 3.5 h (72 V/48 Ah)	Rims	Fr. 1.6×19 or 1.85×18 Rr. 1.85×18 or 2.15×18
Charging power	1080 W	Tires	Fr. 2.25-19 or 2.75-18 Rr. 2.75-18 or 100/80-18
Range*	L1e-B: 115 Km (72 V/48 Ah battery) 68 Km (72 V/32 Ah battery)	Suspension	Hydraulic damping system
	L3e-A1: 104 Km (72 V/48 Ah battery) 68 Km (72 V/32 Ah battery)	Brakes	L1e-B: SSBS L3e-A1: CBS
Max speed	L1e-B: 45 Km/h L3e-A1: 90 Km/h	Colours	Blue, Black

*WMTC Stage 3

Attention: The photos and technical information contained in this catalog may refer to prototypes subject to changes during production and are for purely illustrative and reference purposes, therefore they are not binding for Vmoto International. Vmoto cannot be held responsible for any printing and/or translation errors. This catalog is transnational and therefore some products may not be available and/or their characteristics may vary according to local laws. Not all colors and versions are available in every country. Vmoto reserves the right to make changes and improvements to any product without prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the relevant user manuals. The products represented are not final versions and are therefore subject to significant changes at the discretion of Vmoto without notice. The photographs published in this catalog show only professional drivers in controlled road conditions. Do not try to imitate this driving behavior as it could be dangerous for you or other people on the road. This catalogue, including, but not limited to, trademarks, logos, texts, images, graphics and table of contents, constitutes the intellectual property of Vmoto, or in any case Vmoto has the right to reproduce it; Any total or partial reproduction, modification or other use of the catalog or its contents is prohibited, including publication on the Internet without the prior written consent of Vmoto. Actual battery consumption may vary based on many factors, including, but not limited to, riding style, maintenance performed, weather conditions, surface characteristics, tire pressure, load, rider weight and the passenger, the accessories. Curb weights are considered with all operating fluids, standard equipment and battery. For more information visit www.Vmotosoco.com.

April 2023