



ELECTRIC MOBILITY

REDEFINE YOUR IDEA OF ELECTRIC



Iconic style, top performance, Uncompromised reliability: CPX Explorer is ready to take You on all your adventures.



Thanks to its 8 kW engine, the new CPX Explorer takes the electric riding sensation to another level, with a top speed of 105 km/h and an impressive 100 km range. Form and function have finally found their synthesis. The CPX Explorer becomes even faster thanks to the 8 kW engine, which makes it even more powerful, bringing it up to a speed of 105 km/h. A strong, safe and high-tech vehicle: the perfect partner for your daily dynamics.

Max speed 105 km/h. Range 100 km* Engine Power 8 kW



Scan here for more info

TECHNICAL INFORMATION

Homologation	L3e-A1 (comparable to a 125cc.)		
Engine	VMOTO	LxWxH	2125 mm*760 mm*1430 mm
Rated Power	7 kW	Wheelbase	1366 mm
Maximum Power	8 kW	Ground clearance	154 mm
Battery model	Polymer lithium battery	Seat height	760 mm
Battery capacity	60 V/45 Ah* 2	Rims	Fr. 2.15-16 / Rr. 2.5-14
Charging time	7 h (Double batteries)	Tires	Fr. 100/80-16 / Rr. 110/80-14
Charging power	1050 W	Suspension	Hydraulic damping system
Range*	100 Km	Weight	152 kg
Max. Speed	105 Km/h	Brakes	ABS
Climbing angle	24°	Colours	White / Black / Sky Blue / Red

*Tested at an average speed of 45 km/h; rider weight 75 kg with two batteries.



Happiness is a journey

VMOTO.COM

Vmoto Limited

Level 48, 152-158 St Georges Terrace, Perth Western Australia 6000, Australia

Vmoto International

15, Zhongxing East Road Lishui Economic Development Zone Lishui Discrict, Nanjing 21 1200 Jiangsu Province, China

Vmoto Europe

Boekweitstraat 95-97, 2153 GK Nieuw Vennep, The Netherlands

Vmoto Italy

Sesto S. Giovanni (Milan)

Vmoto Germany

Ammerbuch (Stuttgart)

Vmoto UK

Guildford (London)

Vmoto France

Paris







Attention: The photos and technical information contained in this catalog may refer to prototypes subject to changes during production and are for purely illustrative and reference purposes, therefore they are not binding for Vmoto International. Vmoto cannot be neit responsible for any printing and/or translation errors. This catalog is transnational and therefore some products amy not be available and/or their characteristics may vary according to local laws. Not all colors and versions are available in every country. Vmoto reserves the night to make changes and improvements to any product without prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the relevant user manuals. The products represented are not final versions and are therefore subject to significant changes at the discretion of Vmoto without notice. By products applied in this catalog show only professional drivers in controlled road conditions. Do not try to imitate this driving behavior, in the catalog or the catalog or in any tasse Vmoto and a may be added the controlled or any tasse Vmoto and a may be added the controlled or any tasse Vmoto and the product of the catalog or its contents is prohibited, including publication on the internet without provided to the product of the catalog or its contents is prohibited, including style, main-tenance performed, weather conditions, surface characteristics, the pressure, load, nider weight and the passes for the accessories. Curb weights are considered with all operating fluids, standards equipment and any tasticity, including, but not intented to, rinding style, main-tenance performed, weather conditions, surface characteristics, the pressure, load, nider weight and the passes of the accessories. Curb weights are considered with all operating fluids, standards equipment and with all operating fluids, standards equipment and with all operating fluids, standards equipment and with all operating fluids.